

Steam couplings with safety clamps unit EN 14423/DIN 2826

Luxe's steam couplings complying with EN 14423/ DIN 2826 are available in female & male threaded fittings and in flange couplings. The thread fittings are available in carbon steel, stainless steel or brass. The flange are available in carbon steel or stainless steel.

Application

Luxe's DIN2826 couplings & safety clamps are used for chemicals, food and pharmaceuticals, furnace, offshore and more.

Material

1. Threaded fitting:

- Stainless steel
- Carbon steel
- Brass

2. Clamps:

- Stainless steel
- Brass

3. Flange:

- Carbon steel
- Stainless steel



Thread

1. Steam male thread fitting BSPT
2. Steam female thread fitting BSP



Features



1. Suitable for fixing to steam hoses to BS EN 14423:2004 with safety clamps.
2. Due to the high temperature application in which steam couplings are used, non-asbestos gaskets are used for steam female thread fitting(BSP).



Steam couplings with safety clamps unit
Steam hose fitting EN14423/DIN2826

Luxecasting 2014	Name	Code	Thread	Price USD
Male fitting in stainless steel 	SGA015SS	L1301012	1/2"BSPT	
	SGA020SS	L1301014	3/4"BSPT	
	SGA025SS	L1301013	1"BSPT	
	SGA032SS	L1301011	1 1/4"BSPT	
	SGA040SS	L1301015	1 1/2"BSPT	
	SGA050SS	L1301016	2"BSPT	
Carbon steel 	SGA015CS	L1301006	1/2"BSPT	
	SGA020CS	L1301003	3/4"BSPT	
	SGA025CS	L1301005	1"BSPT	
	SGA032CS	L1301004	1 1/4"BSPT	
	SGA040CS	L1301002	1 1/2"BSPT	
	SGA050CS	L1301001	2"BSPT	
Brass 	SGA015BR	L1301007	1/2"BSPT	
	SGA020BR	L1301008	3/4"BSPT	
	SGA025BR	L1301009	1"BSPT	
	SGA032BR	L1301010	1 1/4"BSPT	
	SGA040BR	L1301017	1 1/2"BSPT	
	SGA050BR	L1301018	2"BSPT	
Female fitting in stainless steel 	SGI015SS	L1392001	G1/2"	
	SGI020SS	L1392002	G3/4"	
	SGI025SS	L1392003	G1"	
	SGI032SS	L1392004	G1 1/4"	
	SGI040SS	L1392005	G1 1/2"	
	SGI050SS	L1392006	G2"	
Carbon steel 	SGI015CS	L1392007	G1/2"	
	SGI020CS	L1392008	G3/4"	
	SGI025CS	L1392009	G1"	
	SGI032CS	L1392010	G1 1/4"	
	SGI040CS	L1392011	G1 1/2"	
	SGI050CS	L1392012	G2"	
Brass 	SGI015BR	L1392013	G1/2"	
	SGI020BR	L1392014	G3/4"	
	SGI025BR	L1392015	G1"	
	SGI032BR	L1392016	G1 1/4"	
	SGI040BR	L1392017	G1 1/2"	
	SGI050BR	L1392018	G2"	





Steam couplings with safety clamps unit Steam clamps EN 14423/DIN 2826

Luxecasting 2014	Name	Code	Hose OD Min-Max/mm	Bolt&Nut	Price USD
	SDN13*6BR	L0604010	24-26	4*M6*20	
	SDN19*7BR	L0604002	32-34	4*M8*25	
	SDN25*7.5BR	L0604003	39-41	4*M8*25	
	SDN32*8BR	L0604004	47-50	4*M8*25	
	SDN38*8BR	L0604005	53-56	4*M10*40	
	SDN50*9BR	L0604006	67-69	4*M10*40	
	SDN13*6SS	L0604001	24-26	4*M6*20	
	SDN19*7SS	L0604009	32-34	4*M8*25	
	SDN25*7.5SS	L0604007	39-41	4*M8*25	
	SDN32*8SS	L0604008	47-50	4*M8*25	
	SDN38*8SS	L0604011	53-56	4*M10*40	
	SDN50*9SS	L0604012	67-69	4*M10*40	

Bolt as in EN ISO 4762,

Nut as in EN ISO 4032.

Steam coupling with safety clamps unit Steam flange EN 14423/DIN 2826

Luxecasting2014	Name	Size	Code	Hose ID mm	Price USD
	SFF15CS	DN15	L1391004	13	
	SFF20CS	DN20	L1391005	19	
	SFF25CS	DN25	L1391006	25	
	SFF32CS	DN32	L1391014	32	
	SFF40CS	DN40	L1391015	38	
	SFF50CS	DN50	L1391016	50	
	SFF15SS	DN15	L1391017	13	
	SFF20SS	DN20	L1391018	19	
	SFF25SS	DN25	L1391019	25	
	SFF32SS	DN32	L1391020	32	
	SFF40SS	DN40	L1391021	38	
	SFF50SS	DN50	L1391022	50	
	SSF15CS	DN15	L1391001	13	
	SSF20CS	DN20	L1391002	19	
	SSF25CS	DN25	L1391003	25	
	SSF32CS	DN32	L1391011	32	
	SSF40CS	DN40	L1391012	38	
	SSF50CS	DN50	L1391013	50	
	SSF15SS	DN15	L1391023	13	
	SSF20SS	DN20	L1391024	19	
	SSF25SS	DN25	L1391025	25	
	SSF32SS	DN32	L1391026	32	
	SSF40SS	DN40	L1391027	38	
	SSF50SS	DN50	L1391028	50	